



TEST REPORT

Page 1 of 4

REPORT NUMBER : TURR150086285

APPLICANT NAME **Birikim Pilleri Batarya San. Tic. Ltd. Şti.**

ADDRESS **Kemankeş Cad. Haliipaşa Sk. No:1/A Karaköy Eminönü İstanbul**

SAMPLE DESCRIPTION : One sample of Battery

DATE IN : 27 May, 2015 (10:05)

DATE OUT : 29 May, 2015

COUNTRY OF ORIGIN : CHINA

MODEL NO : MS614

REQUEST : Battery Directive (2006/66/EC) was performed on the item.

RESULTS : See attachment

CONCLUSION : See attachment

"This report (including any enclosures and attachments) are prepared for the exclusive use of the Customer(s) named in the report and solely for the purpose for which it is provided and on the basis of instructions and information and/or materials supplied by Intertek's Customer. The test results relate only to the specific items tested and are not intended to be a recommendation for any particular course of action. Customer is responsible for acting as it sees fit on the basis of such results. Unless Intertek provide express prior written consent, no part of this report should be reproduced, distributed or communicated to any third party. Intertek do not accept any liability if this report is used for an alternative purpose from which it is intended, nor do Intertek owe any duty of care to any third party in respect of this report. Except where explicitly agreed in writing, all work and services performed is governed by Intertek Standard Terms and Conditions of Service which is available on request or can be obtained at <http://www.intertek.com/terms>."

"The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with ISO/IEC 17025 and TÜRKAK accreditation requirements. Unless otherwise is specified, all Pass or Fail results are given without uncertainty considered. When uncertainty is taken into account, the result may be borderline. Borderline results need to be re-tested to determine their disposition up to customer's decision. Opinions and interpretations expressed herein are outside the scope of TÜRKAK accreditation. Tests marked (*) in this test report are not included in the TÜRKAK accreditation schedule for this laboratory."

Tolga KÜÇÜKKARAAĞAÇ
Coordinator

Neslihan Sözer
Chemical Laboratory Manager



Intertek Test Hizmetleri A.Ş.
Merkez Mahallesi Sanayi Cad. No.23 Altindag Plaza Yenibosna 34197 - ISTANBUL / TURKEY
Phone : +90.212. 496 46 46 Fax: +90.212. 452 80 55
e-mail : intertekcg.turkiye@intertek.com
www.intertek-turkey.com



150086285

PARTS	DESCRIPTION	CONCLUSION
	Sample	
1	BATTERY BODY	PASS
2	BATTERY LEG	PASS

(A) Test Method Summary

Testing Item	Result		Battery Directive Limit (mg/kg)
	Part 1	Part 2	
Cadmium (Cd) Content	ND	ND	0.025% (250 mg/kg)
Lead (Pb) Content	ND	ND	See Note*
Mercury (Hg) Content	ND	ND	2% (20000 mg/kg)

*All batteries, accumulators, and button cells shall be marked with a crossed wheelie bin symbol if they contain more than 0.0005% mercury, or more than 0.002% cadmium or more than 0.004% lead, then the chemical symbol for that particular metal shall be added beneath the crossed wheelie bin symbol. The chemical symbol shall cover an area at least 1,5 % of the surface area of the battery or accumulator and shall have a maximum size of 5 x 5 cm.
Separate chemical symbols are required if the battery or accumulator contains more than one of these metals. For example, a battery containing lead (Pb) exceeding 0.004% and mercury (Hg) exceeding 0.0005%, shall be marked with both the Pb and Hg symbols.

Remarks : ppm=Parts per million based on dry weight of sample
 <=Less than
 ND =Not detected NA =Not applicable NR =Not requested

(B) Test Method :

Testing Item	Testing Method	Reporting Limit
Cadmium (Cd)Content	With reference to IEC 62321-111/116/FDIS,by acid digestion and determined by ICP-OES	2 ppm
Lead (Pb)Content	With reference to IEC 62321-111/116/FDIS,by acid digestion and determined by ICP-OES	2 ppm
Mercury (Hg)Content	With reference to IEC 62321-111/116/FDIS,by acid digestion and determined by ICP-OES	2 ppm



END OF TEST REPORT