

**Model:** Power-Xtra - 2S - 7.4V 8A Li-ion BMS

**Stock Code:** 900.600.501.159

## TECHICAL INFORMATIONS

Item No	Specs / Details		Criteria / Parameters
1	Model	2S - 7.4V 8A Li-ion BMS	2S-8A working current
2	Voltage	Charging voltage	8.4V
3	Current	Maximal continuous charging current	8A
		Maximal continuous discharging current	8A
		Current consumption	≤20μA
4	Overcharge Protection	Over charge detection voltage	4.25V±0.025V
		Over charge detection delay time	0.5~1.8S
		Over charge release voltage	4.05V±0.05V
5	Over Discharge Protection	Over discharge detection voltage	2.80V±0.05V
		Over discharge detection delay time	50—170mS
		Over discharge release voltage	3.0±0.1V
6	Over Current Protection	Over current detection voltage	200±30mv
		Over current detection current	20±5A
		Detection delay time	5mS—15mS
		Release condition	Cut load or Charging Activation
7	Short Circuit Protection	Detection condition	Exterior shot circuit
		Detection delay time	200~500uS
		Release condition	Cut load or Charging Activation
8	Balance	Balance voltage for single cell	-
		Balance current for single cell	-
9	Resistance	Inner resistance	≤50mΩ
10	Temperature	Operating temperature range	-40 ~ +60°C
		Storage temperature range	-55~ +125°C
11	Dimension	Length	48mm
		Width	8mm
		Thickness	2.5mm

**Model:** Power-Xtra - 2S - 7.4V 8A Li-ion BMS

**Stock Code:** 900.600.501.159

## IMAGE / TECHNICAL DRAWING

