

## TECHNICAL INFORMATIONS

Item	Specifications	Conditions
Nominal Voltage	1.2V	
Nominal Capacity	<b>1.300 mAh</b>	Standard charge and Standard discharge
Discharge Cut-off Voltage	1.0V	
Internal Impedance	≤40mΩ	Within 1 hr after standard charge
Charge	Standard	130 mA (0.1C) / Charge at 0.1C for 16 hours / 0°C to 40°C
	Rapid Charge	1.300 mA (1.0C) / ambient temperature of 20±5°C, Relative Humidity: 65±20%
	Trickle Charge	26 ~ 65 mA / (0.02C ~ 0.05C) Ta=-10 ~ 45 °C
Discharge	Standard	260 mA (0.2C) / standard charge, the final voltage is 1.0V
	Rapid Discharge	1.300 mA (1.0C) / standard charge, the final voltage is 1.0V
	Maximum Discharge	<b>1.300 mA ( 1C )</b> Rapid discharge, the final voltage is 0.8V
Over-charge	No leakage nor explosion apacity≥100%	0.2C discharge to 1.0V , 0.1C charge for 48 hrs, then test the Capacity with Standard discharge Conditions
Over-discharge	80%. No leakage nor explosion Capacity≥1040mAh	0.2C discharge to 1.2V,Cornbine the battery with a 4.6Ω electric resistance, after stored for a period of 24 hrs, then test the Capacity with Standard discharge Conditions
Charge-retention Rate	Nominal capacity 60%(780mAh)	Storage a period of 28 days after standard charge, then Standard discharge (0.2C) to 1.0V
Weight	22gr	Approximately
Cycles Test	<b>≥ 500 Cycles</b>	IEC61951-2:2003

## ENVIRONMENT PERFORMANCE

### Storage Temperature

Within 1 Year .....-10°C to 30°C

### Operation Temperature

Standard Charge ..... 0 ~ 40°C

Fast Charge ..... 10 ~ 40°C

Discharge .....-10 ~ 50°C

