

Model: 1.2V 1250 mAh - 4/5AA Battery**Stock Code:** 900.600.503.008

Item	Specifications	Conditions
Nominal Voltage	1.2V	
Nominal Capacity	1250 mAh	
Minimum Capacity	300 min	Standard charge and Standard discharge
Standard Charge	125mA (0.1C)	Ta=0~40°C
	16 hours	Ta=0~40°C
Fast Charge	250 mA (0.2C) ~ 1250 mA (1.0C) with charge termination control	Timer cutoff=110%input capacity Temp. cutoff=40~45°C dT/dt=0.8°C/min(0.5 to 1.0C); hour 0.8~1□/min(1C)
	6.0 hours approx. (0.2C) 1.1 hour approx (1.0C)	
Trickle Charge	25mA (0.02C)~62.5mA (0.05C)	Ta=0~40°C
Discharge Cut-off Voltage	1.0V	
Maximum Discharging Current	3750mA (3.0C)	momentary
Storage Temperature	-20~+25°C (within 1 year) -20~+30°C (within 3 month) -20~+40°C (within 1 month) -20~+50°C (within 1 week)	
Weight	21g	approx
Internal Impedance At 1000 Hz	30m□	Max

Model: 1.2V 1250 mAh - 4/5AA Battery

Stock Code: 900.600.503.008

Representative Image

