




TECHNICAL INFORMATION

Item	Specifications	Conditions
Nominal Voltage	3.65V±0.05V	
Typ. Capacity	4.000 mAh	Discharged Capacity at 1mA, +25°C, 2.0V Cut off
Maximum Recommended Continuous Current	100 mAh	Discharged to 2.0V at + 25°C permitting %50 of the nominal capacity to be achieved
Maximum Pulse Capability	200 mAh	200Mah, 0.1 second pulses drained every 2 min, at 25°C from undischarged cells with 20uA base current, yield voltage readings above 2.7V , the value may vary according to the pulse characteristics, the temperature and the cell's previous history
Configuration	1S1P	
Operating Temperature Range	-55°C+85°C	
Benefits	High voltage, stable during most of the application's lifetime Wide operating temperature range (-55°C+85°C) Low self-discharge rate (less than 1 % per year of storage at + 20°C) Easy integration into compact systems Superior resistance to atmospheric corrosion	
Storage	Stored in clean, dry and cool circumstances (the temperature should be 20° degrees or lower Storage room maintained at a temperature not exceeding 30°C.	
Key features	Stainless steel container and end caps (low magnetic signature) Hermetic glass-to-metal sealing Non-flammable electrolyte Compliant with IEC 86-4 safety standard and IEC 60079-11 intrinsic safety standard Underwriters Laboratories (UL) Component Recognition (File Number MH46165) Non-restricted for transport	
Main applications	Utility metering Automatic meter reading Alarms and security devices Memory back-up Tracking systems Automotive electronics Professional electronics	


REV001-Revised Date:13.06.2022

Dimensions		Cell Image	Battery Pack Drawing
Diameter	18.5± 0.5 mm		
Height	50.5± 0.5 mm		
Connector Model	Molex 51005-0200		
Cable Length	130mm/22AWG		


Typical Discharge Characteristics at 25°C




Voltage and Temperature Curve



Capacity and Current Curve (Cut off with 2.0V)



Discharge Characteristics after storage



REV001-Revised Date:13.06.2022