

### SPECIFICATIONS OF SINGLE CELL

Type	Nickel-Cadmium / Ni-Cd
Model	SC / 2.200mAh

### TECHNICAL INFORMATIONS

Item	Specifications	Conditions
Nominal Voltage	3.6V	
Configuration	<b>3S1P</b>	
Nominal Capacity	2.300 mAh	Standard Charge/Discharge
Minimum Capacity	<b>2.200 mAh</b>	
Standard Charge	220 mA(0.1C) × 16 hrs	Ambient temperature of 20±5°C, Relative Humidity: 65±20%
Rapid Charge	440 mA (0.2C) × 2.6 hrs / approx.	-delta V controlled: 15mV/cell cut-off dT/dt controlled: 1°C per min.
Trickle Charge	0.03C-0.5C	Ta=0 ~ 45°C
Standard Discharge	440mA (0.2C)	to 1.0V/cell
Fast Discharge	1.100 mA(0.5C)	Ta= -20°C ~ 50°C
Maximum Continuous Discharge Current	<b>2.200 mA</b>	<b>1C</b>
Discharge Cut-off Voltage	<b>3.0 V</b>	
Storage Temperature	-20 °C ~ 35°C	Discharged state
Weight	156 gr. / approx.	
Open Circuit Voltage(OCV)	≥3.75V	The open circuit voltage is measured within 1-4 hours after standard charge.
Internal Impedance	≤160mΩ	The initial internal resistance is measured at 1KHz within 1-4 hours after standard charge.
Overcharge	No leakage nor explosion	The overcharge test is measured with a discharge current of 0.2C and a discharge end-off voltage of 1.0V/cell within 1-4 hours after charging for 28 days at a current of 0.1C. Check cell appearance after overcharge.
Charge Retention	Criteria: Discharge capacity ≥ 65% of Nominal Capacity	After standard charge and storage time of 28 days at an ambient temperature of 20°C±2°C, the capacity is measured with a discharging current of 0.2C and a discharge end-off voltage of 3.0V.
Cycles Test	<b>≥500 Cycle</b>	IEC61951-2:2003

## TECHNICAL DRAWINGS

Item	Specifications	Drawings
Thickness / Diameter	23.6 mm	
Width	-	
Length	132.0 mm	
Connector Model	-	
Cable Length	-	
Cable Thickness	-	

### IMAGE



Top View

Front View

Bottom View

All dimen